



HM-500/600/700/800

The best daisy-chain microinverter with
reactive power control for 2 solar panels

Highlights

- Easy installation, just plug and play
- External antenna for stronger communication with DTU
- Power factor (adjustable) 0.8 leading.....0.8 lagging
- Compliant with AS/NZS 4777.2 : 2015 & U.S. NEC 2014/2017 690.12 rapid shutdown
- High reliability; NEMA (IP67) enclosure; 6000V surge protection



Safer



Smarter



More Powerful



More Reliable



sales@hoymiles.com



+86-571-28056101



www.hoymiles.com

Model	HM-500	HM-600	HM-700	HM-800
-------	--------	--------	--------	--------

Input Data (DC)

Commonly used module power (W)	200~310	240~380 ¹	280~440 ¹	320~500 ¹
Peak power MPPT voltage range (V)	27~48	29-48	33~48	34~48
Start-up voltage (V)	22	22	22	22
Operating voltage range (V)	16~60	16-60	16~60	16~60
Maximum input voltage (V)	60	60	60	60
Maximum input current (A)	2*10.5	2*11.5	2*11.5	2*12.5

Output Data (AC)

Rated output apparent power (VA)	500		600		700		800	
Rated output current (A)	2.17	2.08	2.61	2.5	3.04	2.92	3.48	3.33
Nominal output voltage/range (V)	230/180-275 ²	240/180-275 ²	230/180-275 ²	240/180-275 ²	230/180-275 ²	240/180-275 ²	230/180-275 ²	240/180-275 ²
Nominal frequency/range (Hz)	50/45-55 ²		50/45-55 ²		50/45-55 ²		50/45-55 ²	
Power factor	>0.99 default 0.8 leading...0.8 lagging		>0.99 default 0.8 leading...0.8 lagging		>0.99 default 0.8 leading...0.8 lagging		>0.99 default 0.8 leading...0.8 lagging	
Total harmonic distortion	<3%		<3%		<3%		<3%	
Maximum units per branch	10	10	8	8	7	7	6	6

Efficiency

CEC peak efficiency	96.70%	96.70%	96.70%	96.70%
CEC weighted efficiency	96.50%	96.50%	96.50%	96.50%
Nominal MPPT efficiency	99.80%	99.80%	99.80%	99.80%
Nighttime power consumption (mW)	<50	<50	<50	<50

Mechanical Data

Ambient temperature range (°C)	-40~+65
Dimensions (W×H×D mm)	250 x 170 x 28
Weight (kg)	3.0 (including 2.42m AC cable)
Enclosure rating	Outdoor-NEMA (IP67)
Cooling	Natural convection – No fans

Features

Communication	2.4GHz Proprietary RF(Nordic)
Monitoring	Hoymiles Monitoring System
Warranty	12 years standard, 25 years optional
Compliance	EN62109-1/-2, EN61000-6-1/-2/-3/-4, EN61000-3-2/-3, AS/NZS4777.2:2015, EN50549-1, VDE-AR-N 4105:2018

¹ Maximum DC power for each input at 25°C is limited to 350W according to AS/NZS 5033:2014 4.3.12

² Nominal voltage/frequency range can be changed due to the requirements of local power department

High Reliability Based on World's Top Supplier Partners

