

BSLBATT 48V LITHIUM POWER LITHIUM BATTERY

BSLBATT®
Best Solution Lithium Battery

B-LFP48

2.5kWh/5.0kWh/6.6kWh

8.1kWh/10kWh

FEATURES

- 5.12kWh expandable up to 81.92kWh
- AC Coupled for both new and retrofitted installations
- 4.8kW charge and discharge rate
- LiFePo4 cell, safe and environmentally friendly
- Suitable for both indoor and outdoor installation (IP65 rating)
- Premium 10 Year Warranty
- Modular design gives highest flexibility
- 16 Cell lithium batteries as denoted with the voltage 51.2v
- Multiple communication interfaces: RS485, RS232, CAN
- Long life cycle, more than 6000 times
- Safety Cert. RCM, IEC, FCC, TUV, CE, UN38.3, and so on
- Module level auto-balancing
- 0.5C/1C continual charge and discharge
- Proven BMS with widest compatibilities with inverters
- Simple buckle fixing minimize the installation time and cost

APPLICATIONS

- Back-up power
- Self-consumption optimisation
- Off-grid power supply



inquiry@bsl-battery.com



FIELDS OF APPLICATION

- › Hotels
- › Domestic-residential
- › Schools or Institutions
- › Places of public interest
- › Gyms and sports facilities
- › Shops and small businesses
- › Car parks in shopping centres and supermarkets



Lithium battery
BSLBATT

LiFePO₄
Lithium Battery

www.lithium-battery-factory.com



Nominal Parameters

Battery Technology	Lithium iron Phosphate(LiFeP04)				
Model	B-LFP48-50E	B-LFP48-100E	B-LFP48-130E	B-LFP48-160E	B-LFP48-200E
Rated Voltage(V)	51.2	51.2	51.2	51.2	51.2
Rated Capacity(Ah)	50	100	130	160	200
Energy(kWh)	2.5	5.0	6.6	8.1	10.0
Dimension one(mm)	W300*H500*D147	W490*H500*D147	W442*H520*D177	W600*H403.5*D225	W490*H820*D140
Dimension two(mm)	W485*H510*D180	W630*H780*D160			
Weight(Kg)	25	50	60	80	90
Design life(25°C)	10 years				
Cycle life(80°C DOD @25°C)	6000 cycles				

Electrical Characteristics

Voltage Range(V)DC	44.8 to 58.4V DC				
Standard charge current(A)	10A	20A	25A	40A	40A
Standard discharge current(A)	10A	90A	90A	100A	100A
Max continuous charge current(A)	50A	100A	100A	100A	100A
Max continuous discharge current(A)	50A	100A	120A	150A	180A
Battery Pack Round-Trip Efficiency	> 95% (under specific condition)				
Communication Interface	RS232/RS485/CAN				
DC Disconnect	Circuit Breaker, Contactor, Fuse				

Operating Conditions

Installation Location	Indoor / (stand wall-mounted)		
Operating Temperature	Charge	-10 to 45°C	
	Discharge	15 to 30°C	
	Storage	-10 to 45°C	
		25°C	6 months
		45°C	3 months
60°C		1 month	
Humidity	5% to 95%		
Altitude	Max. 2,000m		
Cooling Strategy	Natural Convection		

Certification

Safety	UL1642/CE/RCM/FCC/TUV (IEC 62619) /UL1973
EMC	IEC61000-6-1 , IEC61000-6-3
Hazardous Materials Classification	Class 9
Transportation	UN38.3
IP LEVEL	IP54(IP65 Option)